

## Quad Relay Module



### Introduction

The E-Plex 172QR Quad Relay Module contains four relay contacts in a small, din rail mountable box which connects directly to the E-Plex bus with no special interfacing. Each relay can drive up to 130VAC at 10A with no external components.

The 172QR requires a third bus wire connection to supply power to the relays. The quad relay module's operating range is from 10V to 30V on the E-Plex bus.

### Key Features

- 10 Amp AC/DC switch capacity.
- Self Diagnostics.
- DIN rail mountable.
- 4 independent channels.
- LEN value 3.

### Wiring Specifications

Pin #	Connection Description
1	Relay 1, Contact A
2	Relay 1, Contact B
3	Relay 2, Contact A
4	Relay 2, Contact B
5	Relay 3, Contact A
6	Relay 3, Contact B
7	Relay 4, Contact A
8	Relay 4, Contact B



52 – 54 Riverside, Sir Thomas Longley Road, Medway City Estate, Rochester, Kent ME2 4DP  
tel: +44 (0)1634 711622 fax: +44 (0)1634 290773

email: [sales@e-plex.co](mailto:sales@e-plex.co)  
web: [www.e-plex.co](http://www.e-plex.co)

Important Notice: E-Plex Ltd. (E-Plex) reserves the right to make changes to or discontinue any product or service identified in this publication without notice. E-Plex advises its customers to obtain the latest version of the relevant information to verify, before placing any orders, that the information being relied upon is current. E-Plex assumes no responsibility for infringement of patents or rights of others based on E-Plex applications assistance or product specifications since E-Plex does not possess full access concerning the use or application of customers' products. E-Plex also assumes no responsibility for customers' product designs.